

**Amendments to said Claims:**

Please cancel claims 1 - 23, and append claims 24 - 43.

**Listing of Claims:**

1                   24.     (New) A computer system comprising:  
2                   a first node coupled to a physical disk via a first path;  
3                   a second node coupled to said physical disk via a second path, said second node  
4 being coupled to said first node via a network; and  
5                   a physical disk connecting to a first disk controller and to a second disk controller,  
6 said first disk controller being coupled to said first node via said first path, said second disk  
7 controller being coupled to said second node via said second path,  
8                   each of said first node and said second node comprising:  
9                   a file management table including a file ID and a logical disk ID of a  
10 logical disk, said logical disk being a storage area in said physical disk and storing a file  
11 corresponding to said file ID; and  
12                   a logical disk management table including said logical disk ID, a first path  
13 information designating said first path, and a second path information designating said  
14 second path, said first path information including a first node ID designating said first  
15 node and first status information designating status of said first path, and said second path  
16 information includes a second node ID designating said second node and second status  
17 information designating status of said second path,  
18                   each of said first node and said second node configured to select a path for  
19 accessing said logical disk, if it receives an access request including said file ID, said  
20 path being selected based on said received file ID, said file management table, and said  
21 logical disk management table,  
22                   wherein when said first path becomes unavailable, said first node  
23 configured to respond by:

24 changing said first status information and said second status  
25 information in said logical disk management table in order to change an access  
26 path to said logical disk; and  
27 sending said logical disk ID, said changed first path information,  
28 and said changed second path information to other nodes coupled to said network.

1 25. (New) A computer system of claim 24,  
2 wherein said first node includes a first input/output (I/O) interface via which said  
3 first node is coupled to said first disk controller, and said second node includes a second I/O  
4 interface via which said second node is coupled to said second disk controller,  
5 wherein said first path information further includes a first disk controller ID  
6 designating said first disk controller, and a first I/O interface ID designating said first I/O  
7 interface,  
8 wherein said second path information further includes a second disk controller ID  
9 designating said second disk controller, and a second I/O interface ID designating said second  
10 I/O interface.

1 26. (New) A computer system of claim 24, further comprising a third node  
2 coupled to said first node and said second node via said network, said third node including said  
3 file management table and said logical disk management table,  
4 wherein when said third node detects a fault in said first node, said third node  
5 sends said second node a request for changing an access path to said logical disk,  
6 said second node changes said first status information and said second status  
7 information in said logical disk management table in order to change an access path to said  
8 logical disk, and sends said logical disk ID, said changed first path information, and said changed  
9 second path information to other nodes coupled to said network, and  
10 wherein said other nodes can update their respective logical disk management  
11 tables based on data received from said second node.

1                   27.     (New) A computer system of claim 26,  
2                   wherein if an access request issued from one of said other nodes to said logical  
3 disk times out, then said one of said other nodes selects an access path to said logical disk based  
4 on its updated logical disk management table.

1                   28.     (New) A computer system of claim 26,  
2                   wherein when said third node detects a fault in said first node, said third node  
3 selects a path which becomes unavailable and a corresponding path whose status is waiting, and  
4                   said third node sends said request for changing an access path to said second  
5 node, said second node is coupled to said logical disk via said corresponding path.

1                   29.     (New) A computer system of claim 24,  
2                   wherein one of said other nodes coupled to said network is coupled to a disk  
3 storing a mount construction file, said mount construction file including a node ID designating a  
4 node which exists on a path, and a path status designating a status of said path, and  
5                   said one of said other nodes creates said logical disk management table based on  
6 said mount construction file.

1                   30.     (New) A computer system of claim 29,  
2                   wherein said mount construction file further includes an I/O interface ID  
3 designating an I/O interface which exists on said path, and a disk controller ID designating a disk  
4 controller which exists on said path.

1                   31.     (New) A computer system of claim 30,  
2                   wherein said one of nodes sends said logical disk management table to one or  
3 more of said other nodes coupled to said network.

1                   32.   (New) A computer system of claim 30,  
2                   when said first path becomes unavailable and one of said other nodes receives  
3   said logical disk ID, said changed first path information, and said changed second path  
4   information from said first node, said one of said other nodes updating its mount construction  
5   file.

1                   33.   (New) A computer system of claim 24,  
2                   wherein each of said first node and said second node further includes a buffer  
3   cache for storing data to be written into said logical disk, and  
4                   when said first path becomes unavailable before storing data from said buffer  
5   cache of said first node into said logical disk, said first node sends said data to said second node,  
6   and said second node stores said data into said logical disk via said second path.

1                   34.   (New) A computer system of claim 24,  
2                   wherein said file management table further includes file management information  
3   which is updated based on a received write request,  
4                   when said file management information is updated, each of said first node and  
5   said second node stores said file management table into said physical disk, and  
6                   when said first path becomes unavailable before said updated file management  
7   table in said first node is stored into said physical disk, said first node sends data in said updated  
8   file management table to said second node, and said second node writes said received data into  
9   said physical disk.

1                   35.   (New) A computer system of claim 24,  
2                   wherein each of said first disk controller and said second disk controller includes  
3   a disk cache for storing data to be stored in said physical disk, and  
4                   when said first path becomes unavailable before data stored in said disk cache of  
5   said first disk controller is stored in said physical disk, said second node issues a command for  
6   writing said data in said disk cache into said physical disk via said second disk.

1                   36.     (New) A first node coupled to a second node via a network comprising:  
2                   a first I/O interface for coupling to a physical disk via a first disk controller, said  
3     physical disk coupled to said second node via a second disk controller and a second I/O  
4     interface;  
5                   a file management table including a file ID and a logical disk ID of a logical disk,  
6     said logical disk being a storage area in said physical disk and storing a file corresponding to said  
7     file ID; and  
8                   a logical disk management table including said logical disk ID, a first path  
9     information designating a first path through said first node, and a second path information  
10    designating a second path through said second node, each of said first path information and said  
11    second path information including a node ID designating a node on said path, and a status  
12    information designating availability of said path,  
13                  wherein when said status information of said first path is available and said status  
14    information of said second path is waiting, said first node selects said first path for accessing a  
15    file designated by said file ID which is included in an access request,  
16                  wherein when said first path becomes unavailable, said first node changes said  
17    status information of said first path to unavailable, changes said status information of said second  
18    path to available, and sends said logical disk ID, a changed first path information, and a changed  
19    second path information to said second node in order to change a path used for accessing said  
20    logical disk.

1                   37.     (New) A first node of claim 36,  
2                   wherein said first node is coupled to a disk storing a mount construction file, said  
3     mount construction file including a path status information designating a status of a path and a  
4     node ID designating a node which exists on said path, and  
5                   wherein said first node creates said logical disk management table according to  
6     said mount construction file, and sends it to other nodes coupled to said network.

1                   38.     (New) A first node of claim 37,  
2                   wherein when said first node changes said status information of said first path and  
3     said second path, said first nodes updates said mount construction file.

1                   39.     (New) A first node of claim 36,  
2                   wherein said first node further comprises a buffer cache for storing data to be  
3     written into said logical disk,  
4                   wherein when said first path becomes unavailable before storing data stored in  
5     said buffer cache into said logical disk, said first node sends said data to said second node to  
6     store said data into said logical disk via said second path.

1                   40.     (New) A first node of claim 36,  
2                   wherein said file management table further includes file management information  
3     which is updated based on a received write request,  
4                   wherein when said file management information is updated, said first node stores  
5     said file management table into said physical disk, and  
6                   wherein when said first path becomes unavailable before said updated file  
7     management table is stored into said physical disk, said first node sends data in said updated file  
8     management table to said second node to store said data into said physical disk via said second  
9     path.

1                   41.     (New) A second node coupled to a first node via a network comprising:  
2                   a second I/O interface for coupling to a physical disk via a second disk controller,  
3     said physical disk being coupled to said first node via a first disk controller and a first I/O  
4     interface;  
5                   a file management table including a file ID and a logical disk ID of a logical disk,  
6     said logical disk being a storage area in said physical disk and storing a file corresponding to said  
7     file ID; and

8 a logical disk management table including said logical disk ID, a first path  
9 information designating a first path to said logical disk through said first node, and a second path  
10 information designating a second path to said logical disk through said second node, each of said  
11 first path information and said second path information including a node ID designating a node  
12 on said path, and a status information designating availability of said path,

13 wherein when said status information of said first path is available and said status  
14 information of said second path is waiting, said second node receives an access request including  
15 said file ID and transfers said access request to said first node via said network thereby accessing  
16 said logical disk through said first path,

17 wherein when said first path becomes unavailable, said second node changes said  
18 status information of said first path to unavailable and changes said status information of said  
19 second path to available in order to change a path used for accessing said logical disk.

1 42. (New) A second node of claim 41,

2 wherein when said first node stores data to be written into said physical disk in  
3 said first node and said first path becomes unavailable before said data stored in said first node is  
4 written into said physical disk, said second node receives said data from said first node and  
5 writes said data into said physical disk.

1 43. (New) A second node of claim 42,

2 wherein said first disk controller includes a disk cache for storing data to be  
3 written into said physical disk,

4 wherein when said first path becomes unavailable before data stored in said disk  
5 cache is written into said physical disk, said second node issues a command for writing said data  
6 stored in said disk cache into said physical disk.